

## Model A-22076-PI-F

*Internal Pressure Relief Valve*

*November, 2020*

*Rev. 02*



### TECHNICAL SPECIFICATIONS

- Start-to-Discharge Pressure Setting:  
75 ± 3 psig
- Certified Capacity at Flow Rating Pressure (air): 29,550 scfm
- Max. Vapor-Tight Pressure: 60 psig
- Max. Flow Rating Pressure: 85 psig
- Max. Operating Temperature: 250°F – 600°F (Depending Upon Elastomer Seal Selection)
- Mounting: Standard 10-¼" Bolt Circle, Flat Face
- Mounting Configuration per AAR: aA-1002, Fig. E21A)
- AAR Approval No. PRD122007

NOTE: Alternate O-ring materials are available.



**Model A-22076-PI-F**  
*Internal Pressure Relief Valve*  
November, 2020  
Rev. 02

ITEM	QTY	PART NAME	MATERIAL	PART NO.
1	1	TOP GUIDE WITH INSERT	CARBON STEEL	29-01-XS-P
2	1	VALVE STEM	STAINLESS STEEL	29-02-SS
3	1	RETAINER	CARBON STEEL – NICKEL-PLATED	29-0301-CS-NI
4	1	SAFETY VALVE BODY	CARBON STEEL – NICKEL-PLATED	29-040-CS-NI
5	1	PRV SPRING	STAINLESS STEEL	29-51-SS
6	1	FOLLOWER	CARBON STEEL – NICKEL-PLATED	29-06-CS-NI
7	1	NYLON INSERT LOCKNUT	STAINLESS STEEL	23-8-SS
8	1	O-RING, 2-351	BUNA-N*	29-011-BN
9	1	O-RING, 2-431	BUNA-N*	29-010-BN
10	2	HEX NUT	STAINLESS STEEL	29-012-MO
11	2	HEX-HEAD CAP SCREW	STAINLESS STEEL	29-014-SS
12	2	HEX-HEAD CAP SCREW	STAINLESS STEEL	29-0141-SS
13	1	NAME PLATE	STAINLESS STEEL	29-0761-SS
14	2	DRIVE SCREW	STAINLESS STEEL	763-11-SS
15	1	GASKET	PTFE	29-170-PTFE
16	2	WIRE SEAL KIT	STAINLESS STEEL	22-72-SS
17	1	TUBE ASSEMBLY	CARBON STEEL – NICKEL-PLATED	29-07-CS-NI

\*NOTE: Alternate materials available.

